WALL & SECURITY LIGHTS

# Solar Wall Wash Light RGB 900mm

## Remote

Paint a façade, garden wall or feature fence in colour — no electrician required. This 900mm aluminium wall washer packs 165 red, green and blue LEDs (10W) behind a 14W solar panel and 48Wh LiFePO4 battery, with a 24-key RF remote for colours and effects and a 4-level battery indicator. Rated for 12 hours a night and up to 2 nights per full charge (rated value); actual run time depends on the colour mode and effect.

IP65



## KEY FEATURES

- 10W RGB engine: 55 red, 55 green and 55 blue SMD2835 LEDs.
- 24-button RF433 remote plus on-body button cycling through R, RG, G, GB, B, BR, RGB, flash, strobe, fade and smooth.
- 4-level battery indicator (100/75/50/25%) showing the remaining charge.
- 14W 4V monocrystalline tempered-glass panel, 48Wh LiFePO4 battery; 8–10 hour charge in bright sun; rated 12h × 2 nights per full charge.
- DC input for a 3.65V adaptor or an auxiliary 4–5V solar panel; light sensor with 20 lux threshold.
- Low-battery protection: switches off automatically when the battery voltage is low.
- ABS + PC + aluminium alloy, 900 × 114 × 55mm, IP65; 3-year warranty (battery 24 months).

## APPLICATIONS

Architectural accents, commercial façades, bridge abutments, garden walls, patios and fences, hospitality venues, event spaces and festive displays.

## SPECIFICATIONS

| | |
|---|---|
| Solar panel | 4V 14W monocrystalline, tempered glass, 21–23% efficiency |
| LED | 10W SMD2835, 55 red + 55 green + 55 blue |
| Battery | LiFePO4 48Wh |
| Charging time | 8–10 hours in bright sunshine |
| Lighting time | Rated 12 hours × 2 nights per full charge (rated value; varies with colour mode, sunlight and season) |
| Sensor | Light sensor (20 lux threshold) |
| Control | 24-button RF433 remote; single button colour/mode cycle; 4-level battery indicator |

| | |
|---|---|
| Charging port | DC input: 3.65V adaptor or auxiliary 4–5V solar panel |
| Low-battery protection | Switches off automatically at low battery voltage (can happen after 3–4 cloudy days) |
| Material | High-quality ABS + PC + aluminium alloy |
| Product size | 900 × 114 × 55mm |
| IP rating | IP65 |
| Working temperature | -25°C to 60°C |
| Warranty | 36 months whole unit, 24 months battery |

**Order online**
Choose your version and see prices and delivery at evieko.com.

**Delivered worldwide**
Tracked express courier to your door.

**Bulk & project orders**
Larger quantities and free lighting design on request.

ORDER ONLINE

## Prices, stock & delivery

Scan the code for current prices and delivery to your country. Need larger quantities or a full project? Ask for a quotation and a free lighting design.

**Bulk or project order? Ask us.**

info@evieko.com
+61 404 312 969
evieko.com/pages/request-a-quote